Play value

With our Catamaran, even landlubbers go on a big trip. The childish explorers can rock merrily on the waves, especially when someone stands at the mast and provides a strong wind. A not so brave sailor sits at the tiller and holds the course. You don't fall off even in a heavy gale because you can hold on tightly everywhere. The net between the two gliders not only provides additional fall protection, but also invites you to chill out and observe. After the rest, it's back to fun role-playing games with momentum and movement.





Catamaran


Fundamental characteristics

- Unique and original
- Three-point suspension evokes the illusion of being on a sailing boat
- Incentive for playing: shape, mast guy
- Movement: moving one's centre of gravity, rocking, swinging

Recommended for

- Kindergarten children
- School children
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar





Safety check according to DIN EN 1176

Components

- 2 Hulls incl. rudder
- 1 Mast
- 3 Crossbars
- 1 Net
- 4 Stand posts of robinia

Installation information

Surfacing requirements corresponding to a fall height of ≤ 1.00 m (please refer to price list for more detailed information)

Foundations 4 items 80 x 100 x 80 cm Excavation depth 100 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions. Technical changes reserved.

Technical information

Equipment made of non-impregnated mountain larch / robinia

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Bevel cut

Vertical stand posts with bevelled end grain section as constructive wood preservation measure



Core-free

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape



Hercules rope

Hercules rope, for spliced net connections. A compound of steel rope for the core and polyester or polyamide yarn for the sheath. High abrasion resistance, 4 or 6 strands



Aluminium rope pressing

Aluminium rope pressing, cylindrically pressed, with rounded ends



Universal joint

Drop-forged, hot-dip galvanised universal joint, consists of two sintered bushes, for free swinging in any direction



Profiled washer

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



Adjustable

Adjustable two-piece bolt connection, easy to maintain, no projecting threads



Sintered bush

For all reciprocating movements we use sintered plain bearings which are self-lubricating in use and can easily be exchanged if necessary



Chains

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten



For more detailed explanation of the quality characteristics see price list.

Fittings hot-dip galvanised

Flag made of weatherproof PVC fabric

Dimensions

(small deviations possible)

Length	3.35 m
Width	1.45 m
Seat height	0.65 m
Weight	385 kg

